



RHINO COLOR CODING SHRINK TUBING™



FEATURES

- Color coding of hoses
- Non-Adhesive lined
- Operating temperature range is -57°F to +275°F (-55°C to +135°C)
- Is recommended for use in general purpose applications such as wire marking, color coding of hose assemblies.
- Meets CA Prop 65
- Meets RoHS
- Shrink Ratio: 2:1

BENEFITS

- RCT is a very flexible.
- Flame Resistant
- Meets all of the material and functional requirements of Military Specification AMS-DTL- 23053/5, Class 1 and Class 3.
- Shrink temperature is +90°C / +194°F

Note: We reserve the right to make any engineering or material changes at any time to our products for enhancement, performance and quality.

Proper use of product is the sole responsibility of the user.

Manufactured for Brennan Industries Inc.

SIZING CHART

RCT-1.00 – RCT-4.00 available in the following Colors: Blue (BL), Green (GR), Orange (O), Red (R), White (W) & Yellow (Y)

BRENNAN P/N	Pre-Shrunk I.D.		Will Shrink Down to:		Available Length:*	
	In.	Mm.	In.	Mm.	Ft.	M.
RCT-1.00-	1.00	25.4	0.50	12.70	4	1.219
RCT-1.50-	1.50	38.1	0.75	19.05	4	1.219
RCT-2.00-	2.00	50.8	1.00	25.40	4	1.219
RCT-3.00-	3.00	76.2	1.50	38.10	4	1.219
RCT-4.00-	4.00	101.6	2.00	50.80	4	1.219

RCT-5.00 & RCT-6.00 available only in Clear (CL) – 50 foot rolls

BRENNAN P/N	Pre-Shrunk I.D.		Will Shrink Down to:		Roll Length:	
	In.	Mm.	In.	Mm.	Ft.	M.
RCT-5.00-	5.00	127.0	2.50	63.50	50	15.24
RCT-6.00-	6.00	152.4	3.00	76.20	50	15.24

Ordering Example: Order Qty: BRENNAN P/N: Color
4 pcs. RCT-1.50-BL

* Part Number RCT-1.00 – RCT-4.00 available in 100-foot Reels upon request.

RHINO COLOR CODED TUBING REV.03.2022



IT'S NOT TOUGH, UNLESS IT'S **RHINO TOUGH**

www.rhinosleeve.com

sales@srindustries.us

1-877-744-6602 (1-877-RHINO 02)