



# RHINO SPIRAL GUARD™ HD

## FEATURES & BENEFITS

- Easy to install on loose or mounted hose & cables
- Strong, Flexible, Light Weight
- UV Resistant
- Beveled Edges for Safety
- Temperature Range: -40°F to +280°F (-40°C to +137°C)

## USES

- Preventing hose wear due to friction & abrasion
- Protecting hoses from external forces-harsh environments
- Bundling hoses, cables
- Colors for providing "HIGH" visibility
- Tree Sapling Hose Cover Protection

## MARKETS

- |                              |                        |
|------------------------------|------------------------|
| • Chemical Plants            | • Marinas              |
| • Coal Mining and Processing | • Mining / Quarrying   |
| • Construction               | • Oil / Gas Extraction |
| • Energy / Utilities         | • Petroleum            |
| • Forestry / Logging         | • Railway              |
| • Machinery Manufacturing    | • Robotics             |
| • Manufacturing General      | • Transportation       |
|                              | • Waste Management     |



Meets California Prop 65 & RoHS

## APPLICATIONS



RHINO SPIRAL GUARD HD REV.05.2022

# IT'S NOT TOUGH, UNLESS IT'S **RHINO TOUGH**

[www.rhinosleeve.com](http://www.rhinosleeve.com)

[RhinoSales@Brennaninc.com](mailto:RhinoSales@Brennaninc.com)

1-877-744-6602 (1-877-RHINO 02)





## RHINO SPIRAL GUARD™ HD SIZING

BRENNAN Part Number	I.D.		Opening Range In.	Opening Range Mm.	Carton Size for Black Color		Yellow Length in Feet / Meters	Blue Length in Feet / Meters	Red Length in Feet / Meters
	In.	Mm.			Feet	Meter			
RSG-28HD	0.28	7.1	0.28 - 0.51	7 - 13	495	150.8			
RSG-38HD	0.38	10	0.39 - 0.66	10 - 17	165	50.3	165 / 50.3	165 / 50.3	165 / 50.3
RSG-50HD	0.50	11	0.47 - 0.86	12 - 27	66 & 100	20.1 & 30.48	66 / 20.1	66 / 20.1	66 / 20.1
RSG-62HD	0.62	14	0.62 - 1.06	16 - 30	66 & 100	20.1 & 30.48	66 / 20.1	66 / 20.1	66 / 20.1
RSG-95HD	0.875	20	0.86 - 1.37	22 - 35	66 & 100	20.1 & 30.48	66 / 20.1	66 / 20.1	66 / 20.1
RSG-1.125HD	1.00	25	1.06 - 1.69	27 - 43	66 & 100	20.1 & 30.48	66 / 20.1	66 / 20.1	66 / 20.1
RSG-1.50HD	1.50	32	1.30 - 2.17	33 - 55	66 & 100	20.1 & 30.48	66 / 20.1	66 / 20.1	66 / 20.1
RSG-1.75HD	1.75	38	1.75 - 2.52	42 - 64	66 & 100	20.1 & 30.48	66 / 20.1	66 / 20.1	66 / 20.1
RSG-2.25HD	2.00	50	2.05 - 2.95	52 - 75	66 & 100	20.1 & 30.48	66 / 20.1	66 / 20.1	66 / 20.1
RSG-2.62HD	2.63	60	2.56 - 3.80	65 - 97	66	20.1	66 / 20.1	66 / 20.1	66 / 20.1
RSG-3.00HD	3.00	72	3.15 - 4.30	50 - 110	66	20.1	66 / 20.1	66 / 20.1	66 / 20.1
RSG-4.00HD	4.00	102	3.80 - 4.90	97 - 125	40	12.19	40 / 12.9	40 / 12.9	40 / 12.9
RSG-5.00HD	5.00	127	4.80 - 6.00	122 - 152	27	8.23	27 / 8.23	27 / 8.23	27 / 8.23
RSG-6.00HD	6.00	152	5.70 - 7.00+	145 - 178	20	6.10	20 / 6.1	20 / 6.1	20 / 6.1

\* The following colors (blue, green, red and yellow, etc.) are available 66 feet / 50.29 meters

## CROSS REFERENCE CHART

BRENNAN P/N:	ID	Opening Range in Inches	Available Lengths in Feet	Aeroquip P/N:	Dixon P/N:	F & R P/N:	Gates Global P/N:	Gates P/N:	Parker P/N:	Caplugs/Pigstail P/N:	Safeplast P/N:	Tompkins ProWrap Plus Extreme Duty P/N:	Weather Head P/N:
RSG-28HD	0.28	.28-.51	495	900952-4									
RSG-38HD	0.38	.38-.66	165	900952-6			G80901-0006	7277-1174		R12SSG	012C100Bk	PWP-12	
RSG-50HD	0.50	.47-.86	66/100	900952-8	NFSGX16	93050	G80901-0008	7277-1175		R16SSG	016C100Bk	PWP-16	A9900
RSG-62HD	0.63	.62-1.06	66/100	900952-10	NFSGX20	93063	G80901-0012	7277-1176	HG-075	R20SSG	020C100Bk	PWP-20	A9901
RSG-95HD	0.75	.86-1.37	66/100	900952-12	NFSGX25	93075	G80901-0016	7277-1177	HG-100	R25SSG	025C100Bk	PWP-25	
RSG-1.125HD	1.13	1.06-1.69	66/100	900952-27	NFSGX32	93100	G80901-0020	7277-1178	HG-125	R32SSG	032C100Bk	PWP-32	A9902
RSG-1.50HD	1.50	1.30-2.17	66/100	900952-22	NFSGX40	93125	G80901-0024	7277-1179	HG-150	R40SSG	040C100Bk	PWP-40	A9903
RSG-1.75HD	1.75	1.65-2.52	66/100		NFSGX63	93200	G80901-0028	7277-1180	HG-200	R50SSG	050C100Bk	PWP-50	
RSG-2.25HD	2.25	2.05-2.95	66		NFSGX75	93250	G80901-0036	7277-1181		R63SSG	063C100Bk	PWP-63	
RSG-2.62HD	2.63	2.56-3.80	66		NFSGX90	93300	G80901-0044	7277-1182		R75SSG	075C75Bk	PWP-75	A9904
RSG-3.00HD	3.00	3.15-4.30	66		NFSGX110	93350	G80901-0048	7277-1183	HG-350	R90SSG	090C50Bk	PWP-90	A9905
RSG-4.00HD	3.90	3.80-4.90	40			93400	G80901-0056	7277-1184		R110SSG	110C50Bk	PWP-110	
RSG-4.50HD	4.50	4.50-5.50	40				G80901-0072	7277-0001			235C40Bk		
RSG-5.00HD	5.00	4.80-6.00	27			93500				R140SSG	125C40Bk	PWP-140	
RSG-6.00HD	6.00	5.70-7.00+	20			93600				R160SSG	140C30Bk	PWP-160	

RHINO SPIRAL GUARD HD REV.05.2022



IT'S NOT TOUGH, UNLESS IT'S **RHINO TOUGH**

www.rhinosleeve.com

RhinoSales@Brennaninc.com

1-877-744-6602 (1-877-RHINO 02)